

**Features:**

- Excellent heat transfer technology
- Use Osram Golden Dragon Plus LEDs
- Up to 60% energy saving over incandescent
- Minimum maintenance cost
- Long life of 50,000 hours
- Exclusive optical lensing, good color uniformity
- Water-resistant LED module as IP-66 compliance .
- 2 year warranty



Go green

Selamatkan bumi hemat energi



|  |                             |         |
|--|-----------------------------|---------|
| <b>Model</b>                           | <b>SL-0270VS</b>            |         |
| Input voltage                          | 90~260VAC                   |         |
| LED Consumption                        | Approx. 80W                 |         |
| System Consumption                     | Approx. 95W                 |         |
| LED Luminous Efficiency                | 112Lm/W                     |         |
| LED Initial Flux                       | 5,854 lm (Tj = 25°C)        |         |
| Lamp's Efficiency (%)                  | > 90%                       |         |
| Illumination (E)<br>@13m               | Max                         | 9.6 lux |
|  | Average                     | 7.1 lux |
|  | Min                         | 4.9 lux |
| Color Temperature                      | White: 5,000 ~7,000         |         |
| Color Rendering Index(CRI)             | Typical 70                  |         |
| Light Source                           | 5 Modules Hi-power LED      |         |
| Light Distribution Curve/ Beam Pattern | 120 x 60 degree             |         |
| Junction Temperature(Tj)               | 70 °C ±10 % ( Ta = 25°C)    |         |
| Working Temperature                    | -30°C 50°C                  |         |
| Working Humidity                       | 10% 90% RH                  |         |
| Storage Temperature                    | 10°C 85°C                   |         |
| Working Life                           | 50,000 Hrs                  |         |
| IP Rating                              | IP-66/IP-34                 |         |
| Light Body& Lampshade                  | Aluminum Alloy And PC       |         |
| The Dimensions(Units: mm)              | 720 (L) x 300 (W) x 131 (H) |         |
| Installation pipe                      | 2"                          |         |
| Net Weight                             | Approx. 5.5 Kgs             |         |

Distributor :