



SL-02M SERIES MODULAR LED STREET LIGHT

Features:

- EXPANDABLE UP TO 3 MODULES 16 TO 48W 1150 TO 3450LM
- INDIVIDUAL LED MODULES FOR BETTER HEAT TRANSFER AND EASY REPLACEMENT
- LED MODULES USE OSRAM GOLDEN DRAGON PLUS LEADS
- UP TO 60% ENERGY SAVING OVER INCANDESCENT
- MINIMUM MAINTENANCE COST
- LONG LIFE OF 50,000 HOURS
- EXCLUSIVE OPTICAL LENSING, GOOD COLOR UNIFORMITY
- WATER-RESISTANT LED MODULES AS IP-66 COMPLIANCE .
- AVAILABLE AC 90-264V OR DC 24V
- 2 YEARS WARRANTY



SL-0201M
1 MODULE 16W 1150LM
AC 90-264VAC OR DC 24V



SL-0202M
2 MODULES 32W 2300LM
AC 90-264VAC OR DC 24V



SL-0203M
3 MODULES 48W 3450LM
AC 90-264VAC OR DC 24V

Model	SL-0201M	SL-0202M	SL-0203M
Input voltage	90~260VAC or 24VDC		
LED Consumption (Aprrox)	16W	32W	48W
System Consumption			
LED Luminous Efficiency	112lm/W		
Luminous Flux (at Tj=25°C)	1150 lm	2300 lm	3450 lm
Lamp's Efficiency (%)	> 90%		
Color Temperature	White: 5,000 ~7,000 K		
Color Rendering Index(CRI)	Typical 70		
Light Source	1 pcs LM-1424VS		
Light Distribution Curve/ Beam Pattern	120 x 60 degree		
Junction Temperature(Tj)	70 °C ±10 % (Ta = 25°C)		
Working Temperature	-30°C ~ 50°C		
Working Humidity	10% ~ 90% RH		
Storage Temperature	10°C ~ 85°C		
Working Life	50,000 Hrs		
IP Rating	IP-66/IP-34		
Light Body& Lampshade	Aluminum Alloy And PC with UV stabilizer		
The Dimensions(Units: LxWxH mm)	400 x 210 x 65		600 x 210 x 65
Installation pipe	1.5 "		
Net Weight (Aprrox) kgs	3.0	3.5	4.0
	SL-0201M	SL-0202M	SL-0203M

Authorized Reseller:

